

ELECTRICAL EQUIPMENT

XS Series Tumbler Switch

Features

- Class I, Groups C, D
 - Class II, Groups E, F, G
 - Class III NEMA 7 C D, 9 E F G
- 2-pole 120/277 VAC, 1Ø switch rated at 20A.



Ordering Information


| Item Number | Description |
|-------------|-------------------|
| XS-2C | Cover with Device |

SWB Series Device Bodies

Features

- Single Hub – SWB 1, 2, 3
- Dual Hub – SWB 4, 5, 6
- Class I, Groups C, D
- Class II, Groups E, F, G
- Class III NEMA 7 C D, 9 E F G

For use with XCS, XS, & XT Series Covers
 Ext. Dimensions: 5-7/8L x 3W x 2-1/4"D
 Mounting: 5-1/4 Vertical, 2-1/4 Horizontal



Ordering Information

| Item Number | Hub Information |
|-------------|-----------------|
| SWB-1 | 1/2 Single |
| SWB-2 | 3/4 Single |
| SWB-4 | 1/2 Double |

Junction Box

Features

- Copper-free aluminum
- Cast conduit hubs with bushings
- Blank cover
- Compact size
- Includes 5 hubs and 3 close-up plugs



Ordering Information

| Item Number | Description |
|-------------|---------------------------|
| GRR-2 | 3/4" Opening Junction Box |

Unions



Ordering Information

| Item Number | Hub Size |
|-------------|----------|
| GUM-1 | 1/2" |
| GUM-2 | 3/4" |

Liquid Tight Flexible Conduit



Ordering Information

| Item Number | Description |
|-------------|---------------------------|
| 50-LT | 1/2" Liquid Tight Conduit |
| 75-LT | 3/4" Liquid Tight Conduit |

NOTE: Sold per foot.

Liquid Tight Connectors



Ordering Information

| Item Number | Description |
|-------------|----------------------------------|
| 50LT-ST | 1/2" M. NPT x Liquid Tight |
| 75LT-ST | 3/4" M. NPT x Liquid Tight |
| 50LT-90 | 1/2" M. NPT x Liquid Tight - 90° |
| 75LT-90 | 3/4" M. NPT x Liquid Tight - 90° |