

Inlet Fittings

Application

These inlet fittings are available for assembly into either first stage of single stage regulators. All have 1/4" M. NPT connections and are machined from brass.

Ordering Information

Item Number	Description
970	Hard Nose POL with Wrench Nut
970AX	Hard Nose POL with Wrench Nut and Excess Flow
970AXS	Soft Nose POL with Wrench Nut and Excess Flow
3199W	Heavy Duty Hard Nose POL with Wrench Nut and Excess Flow
970AW	Soft Nose POL with Handwheel
970HT	Soft Nose POL with Handwheel and 60 DMS Orifice
970S	Soft Nose POL with Wrench Nut and 60 DMS Orifice



Item Number	Description
G1653	1/4" MPT x Excess Flow Soft Nose POL with Handwheel
G-1654	1/4" MPT Soft Nose POL with Handwheel
HC5930	POL x 1/4" Barb, 7/8" Hex
G1689	9/16" x 18 LH x Excess Flow POL 7/8" Hex Nut
G1650	9/16" x 18 LH x Full Flow POL 7/8" Hex Nut
G1656	Soft Nose POL with Handwheel x 1/4" Hose (7) Barb
G1655	Excess Flow Soft Nose POL with Handwheel x 1/4" Hose (7) Barb
AM-345	POL x 1/4" M. NPT Angle Inlet Adapter




G1653



HC5930



G1689



G1656



AM-345

Tee Check Manifolds

Application

For use in systems that require uninterrupted gas service during cylinder exchange especially for summer cottages, mobile homes and single appliance loads. Floating disc check minimizes discharge of gas to the atmosphere when empty cylinder is being replaced.

Ordering Information

Item Number	Inlet Connections	Outlet Connection
1350R	F. POL	M. POL
1450R	1/4" Inverted Flare	1/4" M. NPT



Multiple Cylinder Manifolds

Application

Use with suitable pigtails to connect multiple cylinders together. Ideal for loads that require more than one cylinder to be in service at a time. Provides a three-way tee function without an internal disc check.

Ordering Information

Item Number	Inlet Connection	Outlet Connection
1350E	F. POL	M. POL



1350E